

# S 28 NEW



SPECIFICHE PRINCIPALI / TECHNICAL SPECIFICATIONS PRINCIPALES CARACTERISTIQUES TECHNIQUES	S 28 B NEW	S 28 S NEW	S 28 D NEW
Larghezza utile di lavoro (1 spazz.) / Sweeping width (1 brushes) Largeur de balayage (1 brosses)	mm 900	mm 900	mm 900
Larghezza utile di lavoro (2 spazz.) / Sweeping width (2 brushes) Largeur de nettoyage (2 brosses)	mm 1100	mm 1100	mm 1100
Rendimento orario max. / Cleaning capacity up to Rendement jusqu'à	m <sup>2</sup> /h 5000	m <sup>2</sup> /h 6600	m <sup>2</sup> /h 6600
Autonomia di lavoro max / Operating range / Autonomie	h 4	/	/
Capacità contenitore rifiuti / Waste tank capacity Capacité bac de vidange	L 70	L 70	L 70
Superficie filtrante / Filtering surface / Surface filtrante	m <sup>2</sup> 6	m <sup>2</sup> 6	m <sup>2</sup> 6
Velocità di avanzamento / Forward speed Vitesse d'avancement	Km/h 0 - 5	Km/h 0 - 6	Km/h 0 - 6
Pendenza superabile a pieno carico / Max. slope Pente max. surmontable	10 %	10 %	10 %
Rumorosità / Noise level / Bruit	dB 68	dB 75	dB 75
Raggio minimo di sterzata / Turning radius Rayon de virage	mm 1520	mm 1520	mm 1520
SPECIFICHE ALIMENTAZIONE / POWER SPECIFICATIONS DONNEES DE L'ALIMENTATION	S 28 B NEW	S 28 S NEW	S 28 D NEW
Motore di aspirazione / Vacuum motor Moteur d'aspiration	24 v / 180v	/	/
Motore spazzola centrale / Central brush motor Moteur de la brosse centrale	24 v / 650v	12 v / 750v	12 v / 750v
Motore spazzola laterale / Side brush motor Moteur de la brosse latérale	24 v / 100v	12 v / 120v	12 v / 120v
Motore trazione / Traction motor Moteur traction	24 v / 700v	125 OMR hydrost.	125 OMR hydrost.
Alimentazione / Voltage / Alimentation	24 v 4 x 6v 330 Ah	/	/
MOTORIZZAZIONE / MOTORIZATION MOTORISATION	S 28 B NEW	S 28 S NEW	S 28 D NEW
Alimentazione / Feeding Alimentation	Batteria / Battery Batterie	Benzina / Gasoline Essence	Diesel
Potenza - Cilindri / Power - Cylinders / Puissance - Cylindres	/	6 cv / 1 cl	3.7 cv / 1 cl
Raffreddamento / Cooling / Refroidissement	/	aria / air / aérien	aria / air / aérien
DIMENSIONI E PESI / DIMENSIONS & WEIGHT DIMENSIONS ET POIDS	S 28 B NEW	S 28 S NEW	S 28 D NEW
Misure mm: L x l x h / Measures: L x w x h / Mesures: L x l x h	mm 1390 x 875 x 1178	mm 1390 x 875 x 1178	mm 1390 x 875 x 1178
Spazzola centrale / Central brush / Brosse centrale	Ø 265 x 700 mm	Ø 265 x 700 mm	Ø 265 x 700 mm
Spazzola laterale / Side brush / Brosse laterale	Ø 400 mm	Ø 400 mm	Ø 400 mm
Peso macchina a vuoto (senza batteria/acqua/operatore) Weight of the machine (without batteries/water/operator) Poids de la machine (sans batteries/eau/ opérateur)	Kg 270	Kg 336	Kg 336
OPTIONAL	S 28 B NEW	S 28 S NEW	S 28 D NEW
Scarico alto / Hydraulic high dump / Dé chargement hydraulique haut	Elettrico-idraulico / Electric -hydraulic Electro-hydraulique	Elettrico-idraulico / Electric -hydraulic Electro-hydraulique	Elettrico-idraulico / Electric -hydraulic Electro-hydraulique
Altezza scarico / Height dump / Hauteur de décharge	mm 1310	mm 1310	mm 1310
Misure mm: L x l x h / Measures: L x w x h / Mesures: L x l x h	mm 1470 x 915 x 1440	mm 1470 x 915 x 1440	mm 1470 x 915 x 1440

