



<b>SPECIFICHE PRINCIPALI / TECHNICAL SPECIFICATIONS PRINCIPALES CARACTERISTIQUES TECHNIQUES</b>	<b>S 48 B</b>	<b>S 48 D</b>	<b>S 48 DK</b>
Larghezza utile di lavoro (2 spazz.) / Sweeping width (2 brushes) Largeur de balayage (2 brosses)	mm 1800	mm 1800	mm 1800
Larghezza utile di lavoro (1 spazz.) / Sweeping width (1 brushes) Largeur de nettoyage (1 brosses)	mm 1450	mm 1450	mm 1450
Rendimento orario max. / Cleaning capacity up to Rendement jusqu'à	m <sup>2</sup> /h 16200	m <sup>2</sup> /h 21600	m <sup>2</sup> /h 21600
Capacità contenitore rifiuti / Waste tank capacity Capacité bac de vidange	/	/	/
Altezza di scarico / Dumping height Hauteur de décharge	mm 1450	mm 1450	mm 1450
Tipologia filtro (pannello-sacche) / Filter type (panel-bag) Type du filtre (panneau-poche)	sacche / bag poche	sacche / bag poche	sacche / bag poche
Superficie filtrante / Filtering surface Surface filtrante	m <sup>2</sup> 16,8	m <sup>2</sup> 16,8	m <sup>2</sup> 16,8
Velocità di avanzamento / Forward speed Vitesse d'avancement	Km/h 9	Km/h 12	Km/h 12
Pendenza superabile a pieno carico / Max. slope Pente max. surmontable	10 %	13 %	13 %
Rumorosità / Noise level Bruit	dB 80	dB 82	dB 82
Raggio minimo di sterzata / Turning radius Rayon de virage	mm 2400	mm 2400	mm 2400
<b>SPECIFICHE ALIMENTAZIONE / POWER SPECIFICATIONS DONNEES DE L'ALIMENTATION</b>	<b>S 48 B</b>	<b>S 48 D</b>	<b>S 48 DK</b>
Motore di aspirazione / Vacuum motor Moteur d'aspiration	w 800	idraulico/hydraulic hydraulique	idraulico/hydraulic hydraulique
Marca motore / Brand motor Moteur marque	/	Lombardini LDW 1404	Kubota T/1505
Motore spazzola laterale - centrale / Side brush motor - central Moteur de la brosse latérale - central	idraulico / hydraulic hydraulique	idraulico / hydraulic hydraulique	idraulico / hydraulic hydraulique
Tensione di alimentazione / Supply voltage / Alimentation	v 48	/	/
<b>MOTORIZZAZIONE / MOTORIZATION MOTORISATION</b>	<b>S 48 B</b>	<b>S 48 D</b>	<b>S 48 DK</b>
Alimentazione / Feeding Alimentation	/	Diesel	Diesel
Potenza - Cilindri / Power - Cylinders / Puissance - Cylindres	/	cv 17/3600 n° 4	cv 35/3000 n° 4
Raffreddamento / Cooling / Refroidissement	/	acqua / water eau	aria / air aérien
<b>DIMENSIONI E PESI / DIMENSIONS &amp; WEIGHT DIMENSIONS ET POIDS</b>	<b>S 48 B</b>	<b>S 48 D</b>	<b>S 48 DK</b>
Misure mm: L x l x h / Measures: L x w x h / Mesures: L x l x h	2270x1515x1510 mm	2270x1515x1510 mm	2270x1515x1510 mm
Spazzola centrale / Central brush / Brosse centrale	Ø 380 x 1250 mm	Ø 300 x 1250 mm	Ø 300 x 1250 mm
Spazzola laterale / Side brush / Brosse latérale	Ø 560 mm	Ø 560 mm	Ø 560 mm
Peso macchina a vuoto (senza batteria/acqua/operatore) Weight of the machine (without batteries/water/operator) Poids de la machine (sans batteries/eau/ opérateur)	Kg 1500	Kg 1504	Kg 1504

